

# SIPCLEAN 615

## Water Based Cleaner

Product No. 6615

### Features

- Promotes adhesion as it cleans, dramatically improves aged recoatability.
- Reduces repainting costs, no grit sweeping, no roughening up old painted surfaces.
- Biodegradable, contains no solvents, contains no phosphates, halogens or caustics.

### Recommended Use

- Sipcliclean 615 Cleaner was designed to clean intact, painted surfaces in preparation for repainting.
- Experience has shown that it is possible to get the old painted surface "super clean" with Sipcliclean 615 cleaner and no other surface preparation may be needed before repainting. Sanding, solvent wiping, grit sweeping and roughening up the old painted surfaces may be eliminated.
- Sipcliclean 615 Cleaner is ideal for : dry dock painting, maintenance painting, new construction.

### Physical Data

**Appearance** : Clear to slightly hazy  
**Solubility** : Infinite, in fresh or sea water  
**pH** : 11 – 12  
**Viscosity** : 9 – 11 Seconds – Ford Cup 4

**Density** : 1.03 kg/ltr.

**Flash Point** : None

**Boiling Point** : 100°C

**Freezing Point :**

- 4°C
- Does not contain phosphates, halogens, chlorinated solvents or petroleum distillates.
- Does contain water and is biodegradable.

### Specification Date

#### Preparation

All dust and loose materials should be removed for the effective and economic use of Sipcliclean 615. No further surface preparation is required.

## Application Data

### Application Details

For most applications, Sipclean 615 Cleaner can be reduced 2 to 3 times with fresh, clean water. Apply generously by spray, brush, roller or mop. Wait 5 to 10 minutes (but do not allow to dry out), then high pressure wash with fresh water. You must ensure all of the Sipclean 615 Cleaner is removed.

- Scrubbing will aid in removing heavier stains.
- Concentrated Sipclean 615 Cleaner may be required for heavy oil residues.
- If surfaces are hot, pre-wet before application of Sipclean 615 Cleaner.
- Do not apply under freezing conditions.

## Storage Information

### Pack Size

5 and 20 ltr. cans

### Storage

Store generally in original sealed container indoors at a temperature between 5 and 40°C and relative humidity below 70%.

### Shelf Life

2 Years

## Safety Information

### Danger Codes

Sipclean 615 Cleaner is an alkaline cleaner. Care should be taken to prevent eye contact and avoid prolonged or repeated skin contact. During application, the use of eye protection and waterproof gloves is recommended. See the material safety data sheet and product label for complete safety and precaution requirements.

## Disclaimer

The information in this data sheet represent test results or experience under well defined conditions. Its accuracy or suitability under the actual conditions of any intended use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller can not accept any liability in connection with the use of the product relative to coverage, performance, injury or damage, unless we specifically agree in writing to do so. The information in this data sheet is subject to change without notice and it is the user's responsibility to ensure it is current. For further information and advice contact SIPCO Technical Services Department on Tel. (03) 847 2299, Fax (03) 847 3780.